(19) World Intellectual Property Organization

International Bureau



I IODIS CHIADASI II CUBILO IIRII CORII CORSI CHIR I II III COROI IICUI BIDDI 1100 HIBID CHIR CORODA 1101 1100

(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/014126 A1

(51) International Patent Classification⁷:

A63C 9/02

(21) International Application Number:

PCT/AU2004/001070

(22) International Filing Date: 11 August 2004 (11.08.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003904230

11 August 2003 (11.08.2003) Al

- (71) Applicant and
- (72) Inventor: FLETCHER, Nicholas [AU/AU]; 10 Hammerdale Avenue, East St Kilda, VIC 3138 (AU).
- (74) Agents: DREW, David, Charles et al.; 26 Ellingworth Parade, Box Hill, VIC 3128 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SNOWBOARD BINDING



(57) Abstract: A snowboard binding (3) including: (a) a binding base (11) having a front end (12) and a rear end (13); (b) an aperture (14) in the binding base (11) intermediate the front and rear ends (12, 13) for receiving a snowboard engaging member (50) adapted to releasably secure the binding base (11) to a snowboard (1), the perimeter of the aperture (14) including at least one pair of adjacent points (23, 24) adapted for relative movement; and (c) separation means to selectively space the adjacent points (23,24) to loosen the binding base (11) from the board engaging member (50) to enable the binding base (11) to be moved relative to the board engaging means (50), the separation means, preferably including an actuator in the form of a lover operated bolt (4), operably connected to the binding base (11), so that, upon operation of the actuator (4), the perimeter of the aperture (14) is varied to enable the binding base (11) to be released from, and moved relative to, the snowboard engaging member (50) from a first position to a second position in which the binding base (11) may be re-engaged to the snowboard engaging member (50).